

# VITA System 12 Vertical Enclosure, Short (7U)




## FEATURES:

- 19" Rackmount fully compliant to Eurocard and IEEE standards
- 7U x 84HP x 16" (H x W x D)
- 6U vertical card mounting
- 2 to 21 slot VITA-Based System Platforms (VME, VME64x, VPX, VXS, VXI)
- Advanced EMC shielding to meet CE and FCC
- Cooling bottom to top
- Wide range of PSU inputs (90 - 264 VAC, 48 VDC)
- Fixed-mount or front pluggable PSUs with redundant hot swap options
- System monitoring for DC voltages, fan fail and over temp (optional)
- Connector options: 3 Row (96 PIN), 5 Row (160 PIN), 5 Row + PO, RT-2
- Ready to run - turnkey solution


## SCOPE OF SUPPLY

High quality 19" rackmount chassis platform consisting of alodined aluminum enclosures, high performance VITA System, power supply, cooling system and AC/DC power components. Assembled, wired and tested prior to shipment.


## ORDERING INFORMATION



Description	Order Number
<ul style="list-style-type: none"> <li>■ 12.25"(H) x 17"(W) x 15.75"(D)</li> <li>■ Holds 12, 6U x 160mm Cards</li> <li>■ 12 Slot VME or VME64x Backplane</li> <li>■ 4 x 5.25" HH Devices</li> <li>■ 2 x 114 CFM Fans, 12V DC</li> <li>■ 500W: +5V/80A; +12V/12A; 12V/4A, or 600W: +5V/75A; +12V/12A; -12V/4A; 3.3V/40A</li> </ul>	<p>12V12MM578N4VC51</p> <p style="text-align: right;"><b>VME</b></p>
	<p>12V12OP578N4VCF1</p> <p style="text-align: right;"><b>64X</b></p>



Description	Order Number
<ul style="list-style-type: none"> <li>■ 12.25"(H) x 17"(W) x 15.75"(D)</li> <li>■ Holds 21, 6U x 160mm Cards</li> <li>■ 21 Slot VME or VME64x Backplane</li> <li>■ No Device Mounting</li> <li>■ 3 x 114 CFM Fans, 12V DC</li> <li>■ 750W: 5V/120A; +12V/12A; -12V/10A, or 800W: +5V/120A; +12V/12A; -12V/10A; 3.3V/40A</li> </ul>	<p>12V21MMX78N4VC71</p> <p style="text-align: right;"><b>VME</b></p>
	<p>12V21OPX78N4VCH1</p> <p style="text-align: right;"><b>64X</b></p>



**Right Side View**

